

PERMEABLE PAVERS

TYP. NO. 8, 89, OR 9  
AGGREGATE IN OPENINGS

BEDDING COURSE 2 IN. (50 MM)  
THICK (TYP. NO. 8 AGGREGATE)

4 IN. (100 MM) THICK NO. 57  
STONE OPEN-GRADED BASE

SURFACE WATER FLOWS  
THRU BETWEEN PAVERS

SLOPE 1% AWAY FROM  
BUILDING FOR 10 FT. (3 M)

BUILDING WALL

CUT IMPERMEABLE  
LINER FLUSH WITH  
TOP OF PAVERS

OPTIONAL DRAINAGE  
BOARD

30 MIL THICK PVC  
GEOMEMBRANE T/W  
8 OZ. NONWOVEN  
PROTECTIVE  
GEOTEXTILE

MIN. 6 IN. (150 MM) THICK  
NO. 2 STONE SUBBASE

OPTIONAL DRAINAGE  
GEOTEXTILE ON  
SUBGRADE PER DESIGN

PERMEABLE SUBGRADE


EXTEND IMPERMEABLE LINER TO  
BOTTOM OF BUILDING FOUNDATION

BUILDING FOOTING

DISTANCE TO SUIT LOCAL  
GROUND CONDITIONS

NOTE:

1. SELECT GEOTEXTILE PER AASHTO M 288.



# FOUNDATION WALL PROTECTION FROM PERMEABLE INTERLOCKING CONCRETE PVMNT

DRAWING NO.

ICPI-93

SCALE

NO SCALE